

BR2SB649TAQ

/ Descriptions


SOT-89PNP

/ Features


BR2SD669TAQAEC-Q101

/ Applications

/ Equivalent Circuit



/ Pinning




/ hFE Classifications & Marking

|  |   |   |   |
|--|---|---|---|
|  |   |   |   |
|  |   |   |   |
|  | * | * | * |

BR2SB649TAQ


|  |  |  |  |
|--|--|--|--|
|  |  |  |  |
|--|--|--|--|

## / Electrical Characteristic Curve




**BR2SB649TAQ**

/ Marking Instructions



\*\*

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)

 $\pm$  $\pm$  $\pm$  $\pm$ 

### / Resistance to Soldering Heat Test Conditions

 $\pm$  $\pm$ / **Packaging SPEC.**

|  | Units/Reel<br>/ | Reels/Inner Box<br>/ | Units/Inner Box<br>/ | Inner Boxes/Outer Box<br>/ | Units/Outer Box<br>/ | Reel | Inner Box | Outer Box |
|--|-----------------|----------------------|----------------------|----------------------------|----------------------|------|-----------|-----------|
|  |                 |                      |                      |                            |                      |      |           |           |

## / Notices