

/ Descriptions

DFN1006-2L

ESD

DFN1006-2L Plastic Package 1-Line,Bi-directional , ESD Protection Diode.

/ Features

1ns

20KV

IEC61000-4-2

4

ESD

AEC-Q101


Ultra small package, Response Time is Typically < 1 ns, ESD > 20 kV per Human Body Model,IEC61000-4-2 Level 4 ESD Protection, Qualified to AEC-Q101 Standards for High Reliability, HF Product.

/ Applications


MP3

Suitable for cellular phones audio,MP3 players, Digital cameras, Portable devices, mobile telephone and other users, Meet the stringent requirements of automotive applications.

/ Equivalent Circuit



/ Pinning



/ Marking



See Marking Instructions.

Parameter	Symbol	Rating	Unit
Peak Pulse Power($t_p = 8/20\mu s$)	P_{PK}	56	W
Peak Pulse Current($t_p = 8/20\mu s$)	I_{PP}	4	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 20	KV
ESD according to IEC61000-4-2 contact discharge		± 20	
Junction temperature	T_J	125	$^{\circ}C$
Storage Temperature	T_{STG}	-55~+150	$^{\circ}C$

Definitions of electrical characteristics

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
-----------	--------	-----------------	-----	-----	-----	------


/ Electrical Characteristic Curve(Ta=25)




/ Package Dimensions

DFN1006-2L

Unit:mm




/ Marking Instructions



Q
5U

Note	
Q	Automobile halogen-free product Code
5U	Product Type

() /



Note:

- 1

150 200

60 120sec;

1.Preheating:150~200 , Time:60~120sec.
- 2

255±5

5±0.5sec;

2.Peak Temp.:255±5 , Duration:5±0.5sec.
- 3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5℃ Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel /	Reels/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Reel	Inner Box	Outer Box
DFN1006-2L	10,000	10	100,000	6	600,000	7 ×8	180×120×180	390×385×205

/ Notices