

/ Descriptions

TO-252

Schottky Barrier Diode in a TO-252 Plastic Package.


/ Features

High Forward Surge Capability, Ultra Low Forward Voltage Drop, Excellent High Temperature Stability.


/ Applications

For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications.

/ Equivalent Circuit



/ Pinning



PIN1 Anode

PIN 2,4 Cathode

PIN 3 Anode

/ h_{FE} Classifications & Marking

See Marking Instructions.

/ Absolute Maximum Ratings(Ta=25)


Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage Peak Reverse Voltage	V_{RRM} V_{RWM} V_{RM}	200	V
RMS Reverse Voltage	$V_{R(RMS)}$	140	V
Average Rectified Forward Current	$I_{F(AV)}$	10	A
Non Repetitive Peak Surge Current	I_{FSM}	150	A
Junction Temperature Range	$T_{j\ MAX}$	150	°C
Storage Temperature Range	T_{stg}	-55~150	°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse Voltage	V _{BR}	I _R =0.3mA	200			V
Forward Voltage	V _F	I _F =2A T _J =25		0.68	0.75	V
		I _F =2A T _J =125		0.53	0.58	V
		I _F =10A T _J =25		0.87	0.95	V
		I _F =10A T _J =125		0.70	0.75	V
Instantaneous Reverse Current	I _R (Note 1)	V _R =200V T _J =25		4	20	uA
		V _R =150V T _J =125		1.9	5	mA
		V _R =200V T _J =125		3.5	10	mA


/Notes:

1.
 - /Short duration pulse test used to minimize self-heating effect.


/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions



BR

10200

LV

Note:

BR:

10200

LV

****:

TBR


Company Code

Product Type Code.

TBR Process.

Lot No. Code, code change with Lot No.

() /



Note:

- | | | | |
|---|--------|-----------|---|
| 1 | 25 150 | 60 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | 2 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 卷盘	卷盘 盒	只 盒	盒 箱	只 箱		盒	箱
						"		

/ TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 套管	套管 盒	只 盒	盒 箱	只 箱	套管	盒	箱